


Capillary Tubing



STAINLESS STEEL 304, 316, 316L, 321, ASTM A213, ASTM A-269, DIN 17458 CLASS 1, DIN 2462-1

Tolerance: Permissible variations in OD +/- .005" (.13 mm), Wall Thickness +/- 15%

I.D. in mm, listed in center area.

O.D. mm	wall																											
	0.025	0.075	0.080	0.090	0.100	0.125	0.130	0.150	0.175	0.200	0.225	0.250	0.300	0.350	0.375	0.400	0.450	0.500	0.600	0.75	0.80	0.85	1.00	1.25	1.50	2.00	2.50	
0.10	0.05																											
0.20			0.04																									
0.30		0.15	0.14		0.10																							
0.40					0.20																							
0.50					0.30			0.20																				
0.55				0.37																								
0.60					0.40		0.34																					
0.62								0.32																				
0.70						0.45		0.40																				
0.80								0.50	0.45			0.30		0.10														
0.90										0.50																		
1.00					0.80			0.70		0.60		0.50	0.40	0.30														
1.10										0.70																		
1.20										0.80								0.30										
1.30											0.85	0.80																
1.40									1.00																			
1.50							1.20		1.10		1.00		0.80		0.70		0.50											
1.60								1.20			1.00						0.60		0.10									
1.70									1.30																			
1.80											1.30				1.00													
1.90												1.40																
2.00					1.80				1.60		1.50	1.40					1.00											
2.20												1.60										0.50						
2.40															1.60													
2.50									2.10		2.00	1.90			1.70		1.50											
2.60												2.00																
2.80															2.00													
3.00									2.60		2.50						2.00		1.50			1.00						
3.20									2.80							2.40												
3.25																												
3.50															2.75		2.50	2.30										
4.00											3.50						3.00	2.50				2.00	1.50	1.00				
4.50											4.00						3.50											
5.00								4.70	4.60		4.50						4.00	3.50			3.00		2.00					
5.30											4.80																	
5.50																							3.50					
6.00								5.70				5.50				5.20	5.00	4.50	4.40		4.00			3.00	2.00	1.00		